Contura



Contents

Installation of Wi-Fi module	3
Registering an account	4
Add a stove	5
myUplink on multiple mobile devices	9
Updating software in the stove and Wi-Fi module	11
Features, views and settings in the app	14
Colours of the button	18

Download the "myUplink" app by scanning the QR code.









There may be changes to the appearance of the app and differences between iOS and Android.

Registering an account

헙 myU	Jplink	
		E-mail
E-mail		New password
Password	\bigcirc	
		Confirm password
Forge	jot your password?	I accept the <u>terms of service</u>
Log in		I have read and understood the pr
or		
Registe		Next
		< Back
About		▲ Back Inil Telenor SE < Image: 08:17
About		لم Back ۱۱۱ Telenor SE ج کتب 08:17
About	Help JPIINK e about you	A I Telenor SE TO 08:17 Market Description
About	Help JPIINK e about you	ع I Telenor SE کس 18:17 OB:17 Decase check the inbox of your e-main Please check the inbox of your e-main
About	Help	د Back I Telenor SE کر 08:17 Constraints of your e-main of your
About	Help Jpiink e about you ai)	4 A net Telenor SE و کی 08:17 Continue
About Telenor SE 4G 13:46 Tell us some more Full Name Address Line 1 Address Line 2 (Optional ZIP/Postal Code	e about you	A seck Image: Internet sector 08:17
About Telenor SE 4G 13:46 Tell us some more Full Name Address Line 1 Address Line 2 (Optional ZIP/Postal Code	Help	A Seck I Telenor SE TO DEST OB:17 <
About	Help	A series of the second sec
About	Help	A Start Back • I Telenor SE • IM 08:17 • I Telenor SE • IM Im



Add a stove





The light on the Wi-Fi module must be rotating for installation/ pairing with the app to take place. If the light is not rotating, unplug the stove from the mains power and wait for both lights to go out. Plug the stove in again and wait until the light on the stove is solid white and the light on the Wi-Fi module is rotating. (If the stove is connected to Wi-Fi, the light on the Wi-Fi module will be lit up solid.)



2	I Telenor SE Og:12 Create System If your device has a QR code similar to below, press scan the QR code. If your device has a QR code similar to below, press scan the QR code. Scan the QR code
	If you have already connected devices to the internet, press find connected devices





myUplink on multiple mobile devices

Download the "myUplink" app and register a new account as described in a previous chapter. Ensure the stove and mobile device are in the same Wi-Fi network and follow the steps. By having different accounts, you can have different settings for notifications, etc.

1	It appears you don't have any systems. Add System	Image: Telenor SE Image: 09:12 Image: Create System If your device has a QR code similar to below, press scan the QR code. Image: Create System Image: Create System Image: Create System If your device has a QR code similar to below, press scan the QR code. Image: Create System Image: Create System<
3.1	Refresh	If you have already connected your device to the internet, press find connected devices. Find connected devices
	Create System Please select your device. NIBE-06545818034374 NIBE-06765418029501	If there is more than one NIBE number, look on the back of the Wi-Fi device to see which belongs to Contura Connect 556.
	Device not shown? Enter manually Help	



Updating software in the stove and Wi-Fi module

Ensure the stove and mobile device are in the same Wi-Fi network when updating the Wi-Fi module and stove.



2

DO NOT update the stove while it is being used!

Conti	ura Connect 556	~ Conture
Status	5	
Sta	andby	
Current	t state	
Effect	Mode	
Syste	m	
Ä	Notifications	>
\square	History	>
	Main menu	>
	Profile	•
User		
ক্ট্য	Settings	>
?	Help	>
	合	≡

	📲 Telenor SE 奈 💵	14:56		۵ 🗖
3	C Devices		~	Contura
Wi-Fi module	СМО		Versi	on: 1.1.0
	Online		Up to d	ate 🔗
	Contura Connect		Versio	on: 0.9.2
Stove	Online		Update availa	ible 🕁
	谷		≡	

📲 Telenor SE 🗢	09:19			
< System Prof	file	~	Contura	
Name			>	
Address			>	
Devices			•	Ē
Premium			>	
Security			>	
About Service Pa	rtner		>	
Disconnect Syste	im		>	
位		≡		





att	Tele	nor SE 🗢 09:2	.4	•
	<	Firmware Update		Contura
		Updating f	îrmware	
-		CMO / Contu	ra Connect	
-		Version:	X .Y. Z	
		Updat	ting	
1		Almost there, we will let yo	u know when it is r	eady.
_				
		合	≡	

Stove: The software is updating when the button is slowly flashing blue.

Wi-Fi module: The software is updating when the LED ring is rotating.



all 1	Tele	nor SE	ŝ		09:	25				e 🗩
	<	Firm	ware	e Upo	date				*	Contura
			I	Jpda	ting	firm	iwar	e		
_				0.10			0			
			CIVI	Ve	rsion:	ura : X .\	Con (. Z	nec	t	
					Doi	ne				
					Doi	ne				
		1						3	≡	

al Te	elenor SE 奈 09:24	@ 🗖
<	Firmware Update 🗸 🗸	Contura
Г	Updating firmware	
_	CMO / Contura Connect Version: X .Y. Z	
	Restarting the device	

Stove: The update is complete when the button turns to solid white. The update has failed if the light is solid red.

Wi-Fi module: The update is complete when the LED ring turns to solid white.



Restart the stove. Unplug the stove from the mains power, wait for the light to go out, then plug the stove back in to the mains.

Features, views and settings in the app

Add panel



Panel settings





There may be some differences between iOS and Android.

App settings / change language

util Telenor SE 🗢 11:35		2	
Contura Connect 556	✓ Contura	Settings	✓ Contui
Status		Appearance	>
Standby Current state		Profile	>
Effect Mode		About myUplink	>
System		Log out	>
للله المعامة المحافظة محافظة	>		
History	>		
Main menu	>		
Profile	• •		
User			
() Settings	> = ,		
(?) Help	>		
合			≡

3

📲 Telenor SE 🗢	09:19				
Appearance		~	Con	tura	
Language		Eng	lish	~ <	Ē
Theme		Li	ight	~	
Units		Me	tric	~	
位		Ξ			

Main menu



Colours of the button

More information about colours can be found in the Help section of the app.

When the stove is not in operation

Flashing red light:

Something is wrong. Do NOT light the stove! More information can be found in the Messenger menu of the app.

Solid white light:

The stove is in standby. The light goes out when the stove is in operation. Can be selected in LED Settings.

Flashing orange light:

Check the ashpan!

The ashpan probably needs emptying. Reset the alarm by pressing the stove button first, then opening the door. Empty the ashpan, if necessary. If the door is opened first before pressing the stove button, the light will turn green. It will start flashing orange again after approx. 30 minutes. Press the button to reset it. Note that resetting the alarm in the app only shuts the alarm off temporarily.

Solid green light:

The stove is in fire lighting mode and is ready to be lit. The green light goes out when the stove reaches normal operation. (It turns to solid white when "LED always on" is selected.)

When the stove is in operation

Flashing white light:

Time to add firewood. The light goes out when the door is opened.

Solid orange light:

Over-temperature. The stove regulates the temperature automatically. NOTE: No action is required! The light goes out when normal temperature is reached. Read through the fire lighting instructions to light the stove correctly.

Updating software

Rapidly flashing blue light: Press the button to start updating.

Slowly flashing blue light:

Updating in progress.

Solid white light:

Updating complete.

Output settings

Auto (White, can only be selected via the app):

The stove self-regulates the output setting by measuring the room temperature on the rear of the stove.

Low (Yellow):

The stove burns with nominal output and low intensity.

Medium (Orange):

The stove burns with higher output and intensity.

High (Red):

The stove burns with maximum output and intensity.

The colour is confirmed when the light shines solid for 5 seconds.



Contura reserves the right to change dimensions and procedures specified in these instructions without prior notice. The latest version can be downloaded from contura.eu

811515 IAV myUplink App Manual Connect 556 EN-5 2023-06-27