EU Declaration of Conformity

Manufacture									
Manufacturer Address			NIBE AB / Contura Box 134, Skulptörvägen 10 285 23 Markaryd, Sweden info@contura.se www.contura.eu						
Website									
Telephone			+46 433 275100						
THIS DECLARATION OF CONFORMITY	Y IS ISSUEI	O UNDER OUF		-	ITY FOR THE	FOLLOWING	PRODUCT:		
Trade name	Contura 210								
Identification of product			www.contura.eu						
THE OBJECT OF THE DECLARATION I	DESCRIBE			WITH	-				
THE RELEVANT UNION HARMONIZATI			1						
DIR 2009/125/EC			THE RELEVANT HARMONIZED STANDARDS: EN 13240:2001/A2:2004/AC:2007						
REG (EU) 2015/1185			CEN/TS 15883:2010						
REG (EU) 2015/1185 REG (EU) 2015/1186									
REG (EU) 2017/1369 REG (EU) 305/2011									
	No								
Indirect heating functionality:			5,0 kW						
Direct heat output: Energy Efficiency Index (EEI):									
			106,4 KTWA UK 61354 NR 0558						
Test report			KIWA UK 61354, NB 0558						
	PREFERRED		OTHER SUITABL						
FUEL		IEL	FUEL		⁻ η _s (%)	PM	OGC	CO	NO _x
							mg/ Nm ³	(13% 0 ₂)	
Wood logs with moisture content 25%		Yes	No		70,3	40	120	1500	200
ompressed wood with moisture content <12%		No	Yes		70,3	40	120	1500	200
Other woody biomass		No	No						
Non-wood biomass		No	No						
nthracite and dry steam coal		No	No						
lard coke		No	No						
v temperature coke		No	No						
tuminous coal		No	No						
Lignite briquettes		No	No						
Peat briquettes		No	No						
Blended fossil fuel briquettes		No	No						
Other fossil fuel		No	No						
Blended biomass and fossil fuel briquettes	<u> </u>	No	No						
Other blend of biomass and solid fuel No			No						
CHARACTERISTICS WHEN OPERATIN	G WITH TH	E PREFERRE	D FUEL						
ITEM	SYMBOL	VALUE	UNIT	ITE			SYMBOL	VALUE	UNIT
HEAT OUTPUT							ON NET CAL	ORIFIC VALUE	E (NCV)
Nominal heat output:	P _{nom}	5,0	kW		ful efficiency a t output	t nominal	η _{th,nom}	80,3	%
AUXILIARY ELECTRICITY CONSUMPTION				TYPE OF HEAT OUTPUT/ROOM TEMPERATURE CONTROL					
t nominal heat output el _{max} -			kW	Single stage heat output, no room temperature control Yes					
At minimum heat output	el _{min}	-	kW				oom temperatu		No
In standby mode	el _{sb}	-	kW				temperature co		No
	28				h electronic ro				No
							e control plus c	lav timer	No
							e control plus v	-	No
							- 56.16. 51 plus 1		
							presence detect	tion	No
					Room temperature control, with presen Room temperature control, with open w				
					h distance cont				No
Specific precautions for assembly, installation, or maintenance.		t supply of com	/ distances to coml bustion air must a	bustib	le building mat	erials must be			

The undersigned is responsible for the manufacture and conformity with the declared performance.

Steller / peur

Niklas Gunnarsson, Business area manager NIBE STOVES Markaryd, April 1, 2022