EU Declaration of Conformity

Manufacturer	NIBE AB / Contura
Address	Box 134, Skulptörvägen 10
Address	285 23 Markaryd, Sweden
E-Mail	info@contura.se
Website	www.contura.eu
Telephone	+46 433 275100



E-Mail			info@contura.se					lU		
Website			www.contura.eu		V		LUL	IL		
Telephone			+46 433 275100	0						
THIS DECLARATION OF CONFORMIT	TY IS ISSUE	D UNDER OUR	R SOLE RESPONS	SIBILITY	FOR THE	FOLLOWING	PRODUCT:			
Trade name			Contura 35 / 35T	Г						
Identification of product		www.contura.eu								
THE OBJECT OF THE DECLARATION DESCRIBED ABOVE IS IN										
THE RELEVANT UNION HARMONIZAT			THE RELEVANT		ONIZED S	TANDARDS:				
DIR 2009/125/EC		EN 13240:2001/A2:2004/AC:2007								
REG (EU) 2015/1185			CEN/TS 15883:2010							
REG (EU) 2015/1186										
REG (EU) 2017/1369										
REG (EU) 305/2011										
TECHNICAL DOCUMENTATION										
Indirect heating functionality:			No							
Direct heat output:			5,0 kW							
Energy Efficiency Index (EEI):			106,4							
Test report										
гезетероге			140 07 1733,	RRF 40 09 1955, NB 1625						
FUEL	PREFERRED		OTHER SUITAB	BLE	(0/)		IONS AT NOM		1	
		UEL	FUEL	r	1 _s (%)	PM	OGC (No.3	(130/ C)	NO _x	
							mg/ Nm³	(13% 0 ₂)		
Wood logs with moisture content 25%		Yes	No		70,3	40	120	1500	200	
Compressed wood with moisture content	<12%	No	Yes		70,3	40	120	1500	200	
Other woody biomass		No	No							
Non-wood biomass		No	No							
Anthracite and dry steam coal		No	No							
Hard coke		No	No							
Low temperature coke		No	No							
Bituminous coal		No	No							
Lignite briquettes		No	No							
Peat briquettes		No	No							
Blended fossil fuel briquettes	No		No							
Other fossil fuel		No	No							
Blended biomass and fossil fuel briquette	es es	No	No							
Other blend of biomass and solid fuel		No	No							
CHARACTERISTICS WHEN OPERATII	NG WITH T	HE PREFERRE	D FUEL							
ITEM	SYMBO	L VALUE	UNIT	ITEM			SYMBOL	VALUE	UNIT	
HEAT OUTPUT				USEF	UL EFFICII	ENCY, BASED	ON NET CAL	ORIFIC VALUE	(NCV)	
Nominal heat output:	P _{nom}	5,0	kW	Useful heat o	efficiency a utput	t nominal	η _{th,nom}	80,3	%	
AUXILIARY ELECTRICITY CONSUMPT	TION			TYPE	OF HEAT	OUTPUT/ROO	M TEMPERAT	URE CONTRO	L	
At nominal heat output	el	-	kW	Single	stage heat	output, no roo	m temperature	control	Yes	
At minimum heat output	el _{min} -		kW	Two or more manual stages, no room temperature control					No	
In standby mode	el _{sв}	-	kW	With m	nechanic the	ermostat room	temperature co	introl	No	
				With e	lectronic ro	om temperatu	re control		No	
				With e	lectronic ro	om temperatu	re control plus d	lay timer	No	
				With electronic room temperature con		re control plus v				
				OTHE	R CONTRO	OL OPTIONS				
				Room	temperatur	e control, with	presence detect	tion	No	
				Room	temperatur	e control, with	open window de	tection	No	
				With d	istance con	trol option				
Specific precautions for assembly, installation, or maintenance.		nt supply of com	/ distances to comb nbustion air must al							

 $The \ undersigned \ is \ responsible \ for \ the \ manufacture \ and \ conformity \ with \ the \ declared \ performance.$

Niklas Gunnarsson, Business area manager NIBE STOVES

Markaryd, January 1, 2022