EU Declaration of Conformity

Manufacturer	NIBE AB / Contura				
Addison	Box 134, Skulptörvägen 10				
Address	285 23 Markaryd, Sweden				
E-Mail	info@contura.se				
Website	www.contura.eu				
Telephone	+46 433 275100				



E-Mail			info@contura.se							
Website			www.contura.eu			V	IIL	lu		
Telephone			+46 433 275100)						
THIS DECLARATION OF CONFORMIT	Y IS ISSUED	UNDER OUR	SOLE RESPONS	SIBILI	TY FOR THE	FOLLOWING	PRODUCT:			
Trade name			Contura 600 Styl	le-seri	es 610 (A) / 6	20 (T) / 690 (A	/T)			
Identification of product			www.contura.eu							
THE OBJECT OF THE DECLARATION DESCRIBED ABOVE IS IN										
THE RELEVANT UNION HARMONIZAT						TANDARDS:				
DIR 2009/125/EC			THE RELEVANT HARMONIZED STANDARDS: EN 13240:2001/A2:2004/AC:2007							
REG (EU) 2015/1185			CEN/TS 15883:2010							
REG (EU) 2015/1186			CENT 13 13003/E010							
REG (EU) 2017/1369										
REG (EU) 305/2011										
TECHNICAL DOCUMENTATION										
			Ne							
Indirect heating functionality:			No COLW							
Direct heat output:			6,0 kW							
Energy Efficiency Index (EEI):			114,7	ND 1	/ 25					
Test report			RRF 40 17 4615,	, NR T	025					
FUEL	PREFERRED FUEL		OTHER SUITABLE FUEL			EMISSIONS AT NOMINAL HEAT OUTPUT				
					η _s (%)	PM	OGC CO		NO _x	
							mg/ Nm³	(13% 0 ₂)		
Wood logs with moisture content 25%		Yes	No		76,0	40	120	1500	200	
Compressed wood with moisture content <	:12%	No	Yes		76,0	40	120	1500	200	
Other woody biomass		No	No							
Non-wood biomass		No	No							
Anthracite and dry steam coal		No	No							
Hard coke		No	No							
Low temperature coke		No	No							
Bituminous coal		No	No							
Lignite briquettes		No	No							
Peat briquettes		No	No							
Blended fossil fuel briquettes		No	No							
Other fossil fuel		No	No							
Blended biomass and fossil fuel briquettes	5	No	No							
Other blend of biomass and solid fuel		No	No							
CHARACTERISTICS WHEN OPERATIN	IG WITH TH	-								
ITEM	SYMBOL	VALUE	UNIT	ITEI	M		SYMBOL	VALUE	UNIT	
HEAT OUTPUT						NCY, BASED	ON NET CAL	ORIFIC VALUE	(NCV)	
Nominal heat output:	P _{nom}	6,0	kW	Useful efficiency at nominal heat output $\eta_{th,nom}$ 86,0		%				
AUXILIARY ELECTRICITY CONSUMPT	ION			TYF	E OF HEAT	OUTPUT/ROC	M TEMPERAT	URE CONTRO	L	
At nominal heat output	el _{max} -		kW	Single stage heat output, no room to			m temperature	temperature control		
At minimum heat output	el _{min} -		kW	Two or more manual stages, no room tempera			oom temperatu	re control	No	
In standby mode	el _{sb}	-	kW	Witl	n mechanic the	rmostat room	temperature co	ntrol	No	
• -	1			With	n electronic ro	om temperatu	re control		No	
						•	re control plus o	lay timer	No	
				·		•	perature control plus week timer		No	
					HER CONTRO	<u> </u>				
							presence detect	tion	No	
							open window de		No	
					n distance con		,			
Specific precautions for assembly, installation, or maintenance.			distances to comb	ustibl	e building mat	erials must be				

The undersigned is responsible for the manufacture and conformity with the declared performance.

Niklas Gunnarsson, Business area manager NIBE STOVES

Markaryd, January 1, 2022