## **EU Declaration of Conformity**

Manufacturer	NIBE AB / Contura
Addison	Box 134, Skulptörvägen 10
Address	285 23 Markaryd, Sweden
E-Mail	info@contura.se
Website	www.contura.eu
Telephone	+46 433 275100



E-Mail			info@contura.se	5			IIL			
Website			www.contura.eu			V		lU		
Telephone			+46 433 275100							
THIS DECLARATION OF CONFORMIT	Y IS ISSUED	UNDER OUR	SOLE RESPON	ISIBILIT	TY FOR THE	FOLLOWING	PRODUCT:			
Trade name			Contura i40-seri	ies: i40	/ i41 (A/T/S)					
Identification of product			www.contura.eu							
THE OBJECT OF THE DECLARATION DESCRIBED ABOVE IS IN										
THE RELEVANT UNION HARMONIZAT			THE RELEVAN			TANDARDS:				
DIR 2009/125/EC			EN 13240:2001/A2:2004/AC:2007							
REG (EU) 2015/1185			CEN/TS 15883:2010							
REG (EU) 2015/1186 REG (EU) 2017/1369			EN 13229:2001/A2:2004/AC:2007							
REG (EU) 305/2011										
TECHNICAL DOCUMENTATION										
Indirect heating functionality:			No							
Direct heat output:			7,0 kW							
Energy Efficiency Index (EEI):			107,5							
Test report			RRF 29 13 3402	2, NB 16	625					
<u> </u>			OTHER SUITABLE			EWISS	IONS AT NOM	IINAI HEAT O	IITPIIT	
FUEL	PRE	FERRED				PM OGC CO NO,				
	FUE	iL	FUEL		18 (70)	- 1 101		(13% 0)	140 <sub>x</sub>	
					71.0		1			
Vood logs with moisture content 25%		Yes	No		71,0	40	120	1500	200	
compressed wood with moisture content <	12%	No	Yes		71,0	40	120	1500	200	
ther woody biomass	No		No							
lon-wood biomass	No		No							
anthracite and dry steam coal	No		No							
lard coke	No		No							
ow temperature coke	No		No							
Bituminous coal	No		No							
Lignite briquettes		No	No							
Peat briquettes	No		No							
Blended fossil fuel briquettes	No		No							
Other fossil fuel		No	No							
Blended biomass and fossil fuel briquettes			No							
Other blend of biomass and solid fuel		No	No							
CHARACTERISTICS WHEN OPERATIN TEM	SYMBOL			ITEN			OVMBOL	\/A111F	LINUT	
HEAT OUTPUT	STIVIBOL	VALUE	UNIT		USEFUL EFFICIENCY, BASE		SYMBOL	VALUE	UNIT	
HEAT COTFOT		1			ul efficiency a	,	ON NET CAL	OHIFIC VALUE	· (IVCV)	
Iominal heat output:	P <sub>nom</sub>	7,0	kW		output	t Hollillai	η <sub>th,nom</sub>	81,0	%	
AUXILIARY ELECTRICITY CONSUMPTION				TYPE OF HEAT OUTPUT/ROOM TEMPERATURE CONTROL						
t nominal heat output	el	-	kW Single stage heat output, no n			output, no roo	m temperature	Yes		
at minimum heat output	el <sub>min</sub>	-	kW	Two or more manual stages, no roo			·		No	
n standby mode	el <sub>sB</sub>	-	kW	With	With mechanic thermostat room temperature control					
				With	electronic ro	om temperatu	re control		No	
				With	With electronic room temperatur				No	
						ectronic room temperature control plus week timer				
					ER CONTRO	· · · · · · · · · · · · · · · · · · ·				
				Roon	n temperature	control, with	presence detec	tion	No	
				Roon	n temperature	control, with	h open window detection		No	
					distance conf					
Specific precautions for assembly, installa- tion, or maintenance.		-	tances to combustibl tion air must always	le buildir	ng materials mu	st be observed u			ıpply.	

 $The \ undersigned \ is \ responsible \ for \ the \ manufacture \ and \ conformity \ with \ the \ declared \ performance.$ 

Niklas Gunnarsson, Business area manager NIBE STOVES

Markaryd, January 1, 2022