

## Declaration of performance according to Regulation (EU) 305/2011

No. Ci5-CPR-191219

# Contura

### PRODUCT

Type Wood burning insert  
Trade name Contura i5  
Intended area of use Heating of rooms in residential buildings  
Fuel Wood

### MANUFACTURER

Name NIBE AB / Contura  
Address Box 134, Skulptörvägen 10  
SE-285 23 Markaryd, Sweden

### VERIFICATION

According to AVCP System 3  
European standard EN 13229:2001/A2:2004/AC:2007  
Test institute Rein-Ruhr Feuerstätten Prüfstelle, NB 1625.

### DECLARED PERFORMANCE

| ESSENTIAL CHARACTERISTICS                   | PERFORMANCE   | HARMONISED TECHNICAL SPECIFICATION |
|---|---|------------------------------------|
| Fire safety                                 | Pass  | EN 13229:2001/A2:2004/AC:2007      |
| Fire classification                         | A1  |                                    |
| Minimum distance to flammable materials     | Rear: 120 mm (With heat shield)<br>Side: 150 mm (With heat shield)<br>Ceiling: 800 mm<br>Front: 1000 mm<br>Floor: 300 mm<br>Corner: 108 mm (With heat shield) |                                    |
| Fire hazard due to burning fuel falling out | Pass  |                                    |
| Cleanability                                | Pass  |                                    |
| Emissions from combustion                   | CO: 0,1%  |                                    |
| Surface temperatures                        | Pass  |                                    |
| Temperature on the handle                   | NPD   |                                    |
| Mechanical resistance                       | Pass  |                                    |
| Temperature in the space for wood storage   | NPD   |                                    |
| Nominal output                              | 5,0 kW  |                                    |
| Efficiency                                  | 78,0%   |                                    |
| Flue gas temperature at nominal output      | 254°C   |                                    |
| Flue gas temperature in flue spigot         | 269°C   |                                    |

The undersigned is responsible for the manufacture and conformity with the declared performance.



**Niklas Gunnarsson**, Business area manager NIBE STOVES  
Markaryd, December 19, 2019

