PERFORMANCE DECLARATION

No. C556-CPR-130601-SE-1

Contura

PRODUCT

Product type Stove lit with solid biofuels

Type designation Contura 556

Manufacturing number See rating plate on the stove

Intended area of use Heating of rooms in residential buildings

uel Wood

MANUFACTURER

NameNIBE AB / ConturaAddressBox 134, Skulptörvägen 10

SE-285 23 Markaryd, Sweden

CHECKS

According to AVCP System 3

European standard EN 13240:2001 / A2:2004

Test institute Rein-Ruhr Feuerstätten Prüfstelle, NB 1625,

has checked declared performance and issued test report no. RRF-40 10 2345

DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 WT	
Minimum distance to combustible material	100 mm to rear 500 mm to side Other safety distances according to the installation instructions	
Risk of falling embers	Approved	
Emissions from combustion	CO 0.06% NOx 112 mg/m ³ OGC 58 mg/m ³ PM 26 mg/m ³	EN 13240:2001 / A2:2004
Surface temperatures	Approved	
Cleaning options	Approved	
Mechanical durability	Approved	
Emissions of hazardous substances	Approved	
Nominal output	5 kW	
Efficiency	79%	
Flue gas temperature in connector at nominal output	310°C	

The undersigned is responsible for the manufacture and conformity with the declared performance.

Niklas Gunnarsson, Business area manager NIBE STOVES

Markaryd, 1st July 2013