

# Declaration of performance according to Regulation (EU) 305/2011

No. C26T-CPR-220901

# Contura

## PRODUCT

Type Wood burning stove  
Trade name Contura 26T  
Intended area of use Heating of rooms in residential buildings  
Fuel Wood

## MANUFACTURER

Name NIBE AB / Contura  
Address Box 134, Skulptörvägen 10  
SE-285 23 Markaryd, Sweden

## VERIFICATION

According to AVCP System 3  
European standard EN 13240:2001 / A2:2004 / AC:2007  
Test institute Rein-Ruhr Feuerstätten Prüfstelle, NB 1625.

## DECLARED PERFORMANCE

| ESSENTIAL CHARACTERISTICS                   | PERFORMANCE  | HARMONISED TECHNICAL SPECIFICATION |
|---|--|------------------------------------|
| Fire safety                                 | Pass   | EN 13240:2001 / A2:2004 / AC:2007  |
| Fire classification                         | A1   |                                    |
| Minimum distance to flammable materials     | Rear: 100 mm<br>Side: 600 mm<br>Ceiling: 678 mm<br>Front: 1000 mm<br>Floor: 0 mm<br>Corner: 120 mm                     |                                    |
| Fire hazard due to burning fuel falling out | Pass   |                                    |
| Cleanability                                | Pass   |                                    |
| Emissions from combustion                   | CO: 1500 mg/ m <sup>3</sup><br>NOx: 200 mg/ m <sup>3</sup><br>OGC: 120 mg/ m <sup>3</sup><br>PM: 40 mg/ m <sup>3</sup> |                                    |
| Surface temperatures                        | Pass   |                                    |
| Temperature on the handle                   | NPD  |                                    |
| Mechanical resistance                       | Pass   |                                    |
| Temperature in the space for wood storage   | NPD  |                                    |
| Nominal output                              | 6,0 kW   |                                    |
| Efficiency                                  | 79,3%  |                                    |
| Flue gas temperature at nominal output      | 250°C  |                                    |
| Flue gas temperature in flue spigot         | 290°C  |                                    |

The undersigned is responsible for the manufacture and conformity with the declared performance.



**Niklas Gunnarsson**, Business area manager NIBE STOVES  
Markaryd, 1st September 2022

