

Declaration of performance according to Regulation (EU) 305/2011

No. Ci40-CPR-191219

Contura

PRODUCT

Type Wood burning insert
Trade name Contura i40
Intended area of use Heating of rooms in residential buildings
Fuel Wood

MANUFACTURER

Name NIBE AB / Contura
Address Box 134, Skulptörvägen 10
SE-285 23 Markaryd, Sweden

VERIFICATION

According to AVCP System 3
European standard EN 13229:2001/A2:2004/AC:2007
Test institute Rein-Ruhr Feuerstätten Prüfstelle, NB 1625.

DECLARED PERFORMANCE

| ESSENTIAL CHARACTERISTICS | PERFORMANCE | HARMONISED TECHNICAL SPECIFICATION |
|---|--|------------------------------------|
| Fire safety | Pass | EN 13229:2001/A2:2004/AC:2007 |
| Fire classification | A1 | |
| Minimum distance to flammable materials | Rear: 150 mm (With heat shield) Side: 110 mm (With heat shield) Side: 700 mm Ceiling: 550 mm (Front grate) Ceiling: 750 mm (Top grate) Front: 1500 mm Floor: 0 mm Corner: NPD | |
| Fire hazard due to burning fuel falling out | Pass | |
| Cleanability | Pass | |
| Emissions from combustion | CO: 0,07% | |
| Surface temperatures | Pass | |
| Temperature on the handle | NPD | |
| Mechanical resistance | Pass | |
| Temperature in the space for wood storage | NPD | |
| Nominal output | 7,0 kW | |
| Efficiency | 81,0% | |
| Flue gas temperature at nominal output | 273°C | |
| Flue gas temperature in flue spigot | 328°C | |

The undersigned is responsible for the manufacture and conformity with the declared performance.



Niklas Gunnarsson, Business area manager NIBE STOVES
Markaryd, December 19, 2019

