

## Declaration of performance according to Regulation (EU) 305/2011

No. Ci60-CPR-191219

# Contura

### PRODUCT

Type Wood burning insert  
Trade name Contura i60  
Intended area of use Heating of rooms in residential buildings  
Fuel Wood

### MANUFACTURER

Name NIBE AB / Contura  
Address Box 134, Skulptörvägen 10  
SE-285 23 Markaryd, Sweden

### VERIFICATION

According to AVCP System 3  
European standard EN 13229:2001/A2:2004/AC:2007  
Test institute Rein-Ruhr Feuerstätten Prüfstelle, NB 1625.

### DECLARED PERFORMANCE

| ESSENTIAL CHARACTERISTICS                   | PERFORMANCE                                                                                                                                                    | HARMONISED TECHNICAL SPECIFICATION |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Fire safety                                 | Pass                                                                                                                                                           | EN 13229:2001/A2:2004/AC:2007      |
| Fire classification                         | A1                                                                                                                                                             |                                    |
| Minimum distance to flammable materials     | Rear: 90 mm (With heat shield)<br>Side: 500 mm<br>Ceiling: 550 mm (Front grate)<br>Ceiling: 700 mm (Top grate)<br>Front: 1000 mm<br>Floor: 0 mm<br>Corner: NPD |                                    |
| Fire hazard due to burning fuel falling out | Pass                                                                                                                                                           |                                    |
| Cleanability                                | Pass                                                                                                                                                           |                                    |
| Emissions from combustion                   | CO: 0,07%                                                                                                                                                      |                                    |
| Surface temperatures                        | Pass                                                                                                                                                           |                                    |
| Temperature on the handle                   | NPD                                                                                                                                                            |                                    |
| Mechanical resistance                       | Pass                                                                                                                                                           |                                    |
| Temperature in the space for wood storage   | NPD                                                                                                                                                            |                                    |
| Nominal output                              | 6,0 kW                                                                                                                                                         |                                    |
| Efficiency                                  | 81,0%                                                                                                                                                          |                                    |
| Flue gas temperature at nominal output      | 278°C                                                                                                                                                          |                                    |
| Flue gas temperature in flue spigot         | 334°C                                                                                                                                                          |                                    |

The undersigned is responsible for the manufacture and conformity with the declared performance.



**Niklas Gunnarsson**, Business area manager NIBE STOVES  
Markaryd, December 19, 2019

